



Twineye PISA Anchor Nut

Catalog ID: 03G5F2B

Twineye PISA Anchor Nuts are fasteners used for power line hardware systems. It is applied for Pisa Anchor Rods for power and utility requirements. Ultimate strength ratings apply to properly installed anchors only. Hot dipped galvanized per ASTM A153 Eyenut Style: Twineye



PRODUCT DETAILS

General	
Application	Helical Anchoring
Coating	Galvanized, ASTM A-153
Eyenut Style	Twineye
Strength Note	Ultimate strength ratings apply to properly installed anchors only Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	16000 lb
Туре	Power Installed Screw Anchor (PISA)
Dimensions	
Rod Diameter	0.625 in (15.88 mm)
Weight	1.940 lb (0.88 kg)
Logistics	
Pallet Quantity	960
Standard Package	25
RESOURCES AND DOWNLOADS	
Specifications	Download PDF

For further technical assistance, please contact us

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384 Landline: (+86) 22-8523-3528 Cell / WhatsApp: (+86) 155-1086-4645 Email: sales@ttfpower.com Website: https://ttfpower.com