



Uni-Grip Compression Deadend

Catalog ID: 05B8Y6N

Uni-Grip Compression Deadend is a type of overhead line connector. It is designed to secure the completeness of conductors as well as protect other electrical line fittings.
 Conductor compatibility ACSR-Lark-397.5-30/7
 Standard voltage application



PRODUCT DETAILS

General

Bolt Installation Torque (Recommended)	0 ft-lbs
Compression Method	Uni-Grip (single die system)
Die Size	10CD
Material	Aluminum; Steel
Material – Body	Seamless Extruded Aluminum Alloy
Material – Clevis	Galvanized Forged Steel
Material – Hardware	Aluminum Alloy
Material – Pin (Cotter)	#304 Stainless Steel
Material – Terminal	Seamless Extruded Aluminum Alloy
Number of Bolt Holes	2
Number of Pad Holes	0
Product Category	Adjustable Clevis
Style	Uni-Grip, Double Tongue, Adjustable Clevis

Dimensions

Bolt Diameter	0.75 in (19.05 mm)
Diameter – Outside	0.806 in (20.47 mm)
Length Before Compression	21 in (533.4 mm)
Maximum Adjustment	2.9 in (73.66 mm)
Width – Pad	2 in (50.8 mm)

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>