



Uni-Grip Compression Sleeve

Catalog ID: 01C6E9N

Uni-Grip Compression Sleeve is one kind of overhead line connectors used on overhead line construction.

Aluminum Alloy: anti-erosion nature

It is designed to keep the completeness of other power line fittings and hardware for power and utility needs.

Prevent the cracks of other electrical engineering tools

Uni-Grip (single die system)



PRODUCT DETAILS

General

Compression Method	Uni-Grip (single die system)
Die Size	08CD
Material	Aluminum Alloy

Dimensions

Length Before Compression	9.6 in (243.84 mm)
Weight	0.647 lb (0.29 kg)

Electrical Ratings

Voltage Application	Standard
---------------------	----------

Conductor Related

Conductor Compatibility	ACSR-Merlin-336.4-18/1;ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Chickadee-397.5-18/1;ACSR-Brahma-203.2-16/19;AAC-Canna-397.5-19
Conductor Diameter – Maximum	0.765 in (19.43 mm)
Conductor Diameter – Minimum	0.681 in (17.3 mm)
Conductor Diameter Range	0.681 – 0.765

RESOURCES AND DOWNLOADS

Specifications	Download PDF
Technical Drawings	Download PDF

For further technical assistance, please contact us

TTF Power Technology Co., Ltd.

Office: Rm. 609-610 Tianjin Technology Financial Bldg., Tianjin, China, 300384

Landline: (+86) 22-8523-3528

Cell / WhatsApp: (+86) 155-1086-4645

Email: sales@ttfpower.com

Website: <https://ttfpower.com>