



CATALOG NUMBER : 01B3B5D



NOTES:

- 1.MATERIAL: TIN PLATED ALUMINUM.
- 2.PARTS MEET UNDERWRITER'S LABORATORY APPROVAL FOR UL486B90°C & HV RATING.
- 3.PARTS ARE FURNISHED PREFILLED WITH A "VERSA-SEAL" INHIBITOR.
- 4.PARTS ARE C.S.A. APPROVED.

CATALOG NUMBER	STRAND CONDUCTOR SIZE(S)		MOUNTING BOLT SIZE (METRIC)	FIG.	DIMENSIONS IN INCHES (MILLIMETERS)					
	FOR ANDERSON VERSA-CRIMP COMPRESSION TOOL(S)	FOR OTHER RECOMMENDED COMPRESSION TOOLS			A	C	D	E	H	L
01B3B5D_1 01B3B5D_2	#8 STR. AL-CU (VC6-L & VC6-350 ONLY)	#8 AL-CU	#10 (5) 1/4" (6.4)	1	7/8 (22.2)	1/2 (12.7)	11/16 (17.5)	1/8 (3.2)	--	1-7/8 (47.6)
01B3B5D_3 01B3B5D_4	#6 STR. AL-CU (VC6-L & VC6-350 ONLY)	#6 AL-CU	#10 (5) 1/4" (6.4)	1	7/8 (22.2)	1/2 (12.7)	11/16 (17.5)	1/8 (3.2)	--	1-7/8 (47.6)
01B3B5D_5 01B3B5D_6 01B3B5D_7	#4 STR. AL-CU (VC6-L & VC6-350 ONLY)	#4 AL-CU	1/4" (6.4) 5/16" (8) 3/8" (10)	1	1 (25.4)	13/16 (20.6)	13/16 (20.6)	1/8 (3.2)	--	2.27 (57.7)
01B3B5D_8 01B3B5D_9 01B3B5D_10	#6 - #2 AL-CU	#2 AL-CU	1/4" (6.4) 5/16" (8) 3/8" (10)	1	1-1/8 (28.6)	7/8 (22.2)	7/8 (22.2)	3/16 (4.8)	--	2-1/2 (63.5)
01B3B5D_11 01B3B5D_12	#8 - #1 AL-CU	#1 AL-CU	5/16" (8) 3/8" (10)	1	1-5/16 (33.3)	13/16 (20.6)	1-1/8 (28.6)	1/4 (6.4)	--	2-15/16 (74.6)
01B3B5D_13 01B3B5D_14 01B3B5D_15 01B3B5D_16 01B3B5D_17	#8 - 1/0 AL-CU	1/0 AL-CU	5/16" (8) 3/8" (10) 1/2" (12) 3/8" (10) 1/2" (12)	1 1 1 2 2	1-5/16 (33.3)	13/16 (20.6)	1-1/8 (28.6) 1-1/8 (28.6) 1-5/16 (33.3) 2-3/16 (55.5) 3-1/16 (77.8)	3/16 (4.8) -- -- 1-1/16 (27) 1-3/4 (44.4)	-- -- -- 4 (101.6) 4-7/8 (123.8)	

DRN BY:	DATA
Ella	08/06/17
<small>CONFIDENTIAL THIS DRAWING AND ITS CONTENTS PROPERTY OF TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO.,LTD. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO.,LTD. TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO.,LTD UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</small>	

ALUMINUM COMPRESSION TERMINAL



TTF POWER TECHNOLOGY CO.

CATALOG NUMBER : 01B3B5D

CATALOG NUMBER	STRAND CONDUCTOR SIZE(S)		MOUNTING BOLT SIZE (METRIC)	FIG.	DIMENSIONS IN INCHES (MILLIMETERS)						
	FOR ANDERSON VERSA-CRIMP COMPRESSION TOOL(S)	FOR OTHER RECOMMENDED COMPRESSION TOOLS			A	C	D	E	H	L	
01B3B5D_18	#4-2/0 AL-CU	2/0 AL-CU	3/8" (10)	1	1-5/16 (33.3)	15/16 (238.)	1-1/8 (28.6)	1/4 (6.4)	--	2-15/16 (74.6)	
01B3B5D_19			1/2" (12)	1			1-5/16 (33.3)		--	3-1/8 (79.4)	
01B3B5D_20			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	4-7/8 (123.8)	
01B3B5D_21	#4-3/0 AL-CU	3/0 AL-CU	3/8" (10)	1	1-5/16 (33.3)	1-1/16 (27)	1-1/8 (28.6)	1/4 (6.4)	--	3 (76.2)	
01B3B5D_22			1/2" (12)	1			1-5/16 (33.3)		--	3-3/16 (81)	
01B3B5D_23			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	4-15/16 (125.4)	
01B3B5D_24	#2-4/0 AL-CU	4/0 AL-CU	3/8" (10)	1	1-1/2 (38.1)	1.24 (31.5)	1-1/8 (28.6)	.26 (6.6)	--	3-5/16 (84.1)	
01B3B5D_25			1/2" (12)	1			1-5/16 (33.3)		--	3-1/2 (88.9)	
01B3B5D_26			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	5-1/4 (133.3)	
01B3B5D_27	1/0-250 MCM AL-CU	250 MCM AL-CU	1/2" (12)	1	1-1/2 (38.1)	1-1/4 (31.7)	1-5/16 (33.3)	5/16 (7.9)	--	3-9/16 (90.5)	
01B3B5D_28			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	5-5/16 (134.9)	
01B3B5D_29	1/0-300 MCM AL-CU	300 MCM AL-CU	1/2" (12)	1	1-1/2 (38.1)	1-3/8 (34.9)	1-5/16 (33.3)	3/8 (9.5)	--	3-3/4 (95.2)	
01B3B5D_30			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	5-1/2 (139.7)	
01B3B5D_31	2/0-350 MCM AL-CU	350 MCM AL-CU	1/2" (12)	1	1-5/8 (41.3)	1-1/2 (38.1)	1-5/16 (33.3)	3/8 (9.5)	--	4-1/16 (103.2)	
01B3B5D_32			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	5-13/16 (147.6)	
01B3B5D_33	3/0-400 MCM AL-CU	400 MCM AL-CU	1/2" (12)	1	1-13/16 (46)	1-5/8 (41.3)	1-5/16 (33.3)	7/16 (11.1)	--	4-1/4 (107.9)	
01B3B5D_34			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	6 (152.4)	
01B3B5D_35	4/0-500 MCM AL-CU	500 MCM AL-CU	1/2" (12)	1	2-5/16 (58.7)	1-11/16 (42.9)	1-5/16 (33.3)	3/8 (9.5)	--	4-11/16 (119)	
01B3B5D_36			5/8" (16)	1			1-13/16 (46)		--	5-3/16 (131.8)	
01B3B5D_37			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	6-7/16 (163.5)	
01B3B5D_38	350-500 MCM AL-CU	600 MCM AL	5/8" (16)	1	2-15/16 (74.6)	1-7/8 (47.7)	1-5/16 (33.3)	7/16 (11.1)	--	5-7/8 (149.2)	
01B3B5D_39			350-600 MCM AL	1/2" (12)			2		3-1/16 (77.7)	1-3/4 (44.4)	7-1/8 (181)
01B3B5D_40	500 MCM CU	750 MCM AL	1/2" (12)	1	2-15/16 (74.6)	1-5/16 (33.3)	1-5/16 (33.3)	5/16 (7.9)	--	5-3/8 (136.5)	
01B3B5D_41			500-750 MCM AL	5/8" (16)			1		1-13/16 (46)	--	5-7/8 (149.2)
01B3B5D_42			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	7-1/8 (181)	
01B3B5D_43	750-1000 MCM AL-CU	1000 MCM AL	5/8" (16)	1	2-3/4 (69.8)	2-5/8 (66.7)	1-5/16 (33.3)	11/16 (17.5)	--	6-9/16 (166.7)	
01B3B5D_44			1/2" (12)	2			3-1/16 (77.7)		1-3/4 (44.4)	7-13/16 (198.4)	

DRN BY:	DATA
Ella	08/06/17
<small>CONFIDENTIAL-THIS DRAWING AND ITS CONTENTS PROPERTY OF TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO.,LTD. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO.,LTD. TIANJIN TUOFA ELECTRIC POWER TECHNOLOGY CO.,LTD UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</small>	

ALUMINUM COMPRESSION TERMINAL



TTF POWER TECHNOLOGY CO.